

# Quarkus - Kubernetes Config

Quarkus includes the `kubernetes-config` extension which allows developers to use Kubernetes `ConfigMaps` as a configuration source, without having to mount the `ConfigMaps` into the `Pod` running the Quarkus application.

## Configuration

Once you have your Quarkus project configured you can add the `kubernetes-config` extension by running the following command in your project base directory.

```
./mvnw quarkus:add-extension -Dextensions="kubernetes-config"
```

This will add the following to your `pom.xml`:

```
<dependency>
  <groupId>io.quarkus</groupId>
  <artifactId>quarkus-kubernetes-config</artifactId>
</dependency>
```

## Usage

The extension works by reading `ConfigMaps` directly from the Kubernetes API server using the `Kubernetes Client`.

The extension understands the following types of `ConfigMaps` as input sources:

- `ConfigMaps` that contain literal data (see [this](#) for an example on how to create one)
- `ConfigMaps` created from files named, `application.properties`, `application.yaml` or `application.yml` (see [this](#) for an example on how to create one).

To configure which `ConfigMaps` (from the namespace that the application runs in, or the explicitly configured namespace via `quarkus.kubernetes-client.namespace`), you can set the `quarkus.kubernetes-config.config-maps` property (in any of the usual Quarkus ways). Keep in mind however that you will also have to explicitly enable the retrieval of `ConfigMaps` by setting `quarkus.kubernetes-config.enabled=true` (the default is `false` in order to make it easy to test the application locally).

## Priority of obtained properties


The properties obtained from the `ConfigMaps` have a higher priority (i.e. they override) any properties of the same name that are found in `application.properties` (or the YAML equivalents), but they have lower priority than properties set via Environment Variables or Java System Properties.

# Kubernetes Permissions

Since reading ConfigMaps involves interacting with the Kubernetes API Server, when [RBAC](#) is enabled on the cluster, the [ServiceAccount](#) that is used to run the application needs to have the proper permissions for such access.

Thankfully, when using the [kubernetes-config](#) extension along with the [Kubernetes](#) extension, all the necessary Kubernetes resources to make that happen are automatically generated.

## Configuration Reference

 Configuration property fixed at build time - All other configuration properties are overridable at runtime

Configuration property	Type	Default
<a href="#">quarkus.kubernetes-config.enabled</a> If set to true, the application will attempt to look up the configuration from the API server	boolean	<b>false</b>
<a href="#">quarkus.kubernetes-config.fail-on-missing-config</a> If set to true, the application will not start if any of the configured config sources cannot be located	boolean	<b>true</b>
<a href="#">quarkus.kubernetes-config.config-maps</a> ConfigMaps to look for in the namespace that the Kubernetes Client has been configured for	list of string	